

7S7P 119Ah Battery Pack

UNDERWATER POWER SOURCE




The EvoLogics 7S7P non-rechargeable underwater battery pack is a high-capacity depth-rated power solution for long-term subsea deployments. The battery is optimized for the pulsing load of underwater acoustic modems.

Li-CFX / MnO₂ Hybrid cells with high energy density ensure high-performance and long operating life. Robust corrosion-free housing is reusable and allows to replace the battery pack once the cells are discharged.

The **applications** include:

- Subsea observatories
- Autonomous underwater equipment
- Underwater sensor networks

GENERAL	HOUSING MATERIAL	Delrin or Titanium
	DEPTH RATING	200 m (Delrin), 6000 m (Titanium)
	CONNECTOR TYPE	Subconn 6-pin connector FCR1506F
BATTERY	CELL TYPE	Ultralife UHR-XR34610 primary (non-rechargeable) battery
	CELL CHEMISTRY	Li-CFX / MnO ₂ Hybrid
	BATTERY CONSTRUCTION	7S7P
	BATTERY CAPACITY	119 Ah / 2500 Wh
VOLTAGE	NOMINAL VOLTAGE	21 V
	MAXIMUM VOLTAGE	23.1 V
	END-OF-DISCHARGE VOLTAGE (EODL)	18 V
DIMENSIONS <small>without handles</small>		L 53 x Ø 15 cm
WEIGHT <small>dry/wet</small>		Delrin: 11.0 / 1.7 kg; Titanium: 19.75 / 10.7 kg
OPERATING TEMPERATURE RANGE		-30°C to +55°C
STORAGE TEMPERATURE RANGE		-40°C to +55°C



FCR1506F

PIN	DESCRIPTION
1	BAT+
2	BAT+
3	NC
4	BAT-
5	BAT-
6	NC

Please refer to Ultralife UHR-XR34610 documentation for more information on the battery cells.

Specifications subject to change without notice. © EvoLogics GmbH - June 2020